























d 750~1620mm

Boundary Dimensions									Basic Load Ratings		Limiting Speeds	
<i>d</i>	<i>d</i> <sub>1</sub>	<i>D</i>	<i>D</i> <sub>1</sub>	<i>B</i>	<i>C</i>	<i>H</i>	<i>S</i>	<i>r</i> <sub>min</sub>	Dynamic <i>C</i>	Static <i>C</i> <sub>0</sub>	Grease	Oil
mm									kN		r/min	
750	964	1280	1183	122	152	315	436	15	159000	70800	140	200
800	1034	1360	1310	120	165	335	462	15	2000	91000	130	180
1060	1180	1400	1300	128	103	206	566	12	10500	58500	120	160
	1200	1400	1325	66	103	206	566	9.5	10500	58200	120	160
	1349	1770	1615	192	207	426	610	15	32200	148000	100	150
1180	1330	1520	1452	83	101	206	625	9.5	9900	56900	110	160
1320	1380	1540	1510	87	72	175	1446	6	4050	50400	70	90
1620	1700	1860	1799	45	80	150	850	6	6150	48400	50	70

Bearing Designations		Minimum Load Constant <i>A</i>	Mounting Dimensions			Mass
Present	Original		<i>d</i> <sub>a</sub>	<i>D</i> <sub>a</sub>	<i>r</i> <sub>max</sub>	
			mm			kg
294/750		590	1000	1130	12	1650
294/800		680	1080	1185	12	1870
906921/1060	90692/1060	300	1225	1290	8	824
292/1060EF		300	1225	1290	8	784
294/1060EF/HC			1360	1570	10	3973
292/1180EF			1270	1430	8	855
691/1320	691/1320	140	1430	1470	8	480
292/1620			1740	1780	10	552